

HSF

NOTES:
 Rated Current: See the table below. Δ
 Contact Resistance: 25m Ω Max.
 Withstand Voltage: 500V
 Insulation Resistance: 10000M Ω Min.
 Operation Temperature: -55°C to +125°C

Contact Material: Copper Alloy
 Contact Plating: Sn and Au over Ni
 Tail Material: Copper Alloy
 Tail Plating: Sn over Ni
 Main Body Material: High Temperature Thermoplastic(UL94V-0)

Ordering Information

3910- S XXX - 062 M XX W R X W




No. of Pins
 010: 10 Pin
 020: 20 Pin
 100: 100 Pin

Plating Δ
 S3=Sel.10U" Gold/Tin
 S4=Sel.15U" Gold/Tin
 S5=Sel.30U" Gold/Tin


Package
 R: Tape & Reel+Cap
 Blank=W/O WCON
 W=W/T WCON

Contact Material	PART NO.	No. of Pins	Rated Current (Max.): A (20°C ambient temperature)
C5191	3910-SXXX-062MXXWR1(W)	< 30P	2.16A
		30~50P	1.8A
		> 50P	1.44A
C7025	3910-SXXX-062MXXWR7(W)	< 30P	3.36A
		30~50P	2.8A
		> 50P	2.24A

PIN	M
10~40PIN	0.10
42~100PIN	0.15



Recommended P.C.B Layout(Top Side)
 (PCB BOARD TOLERANCE±0.05)



LOGO左右居中 Δ

B1	2023/12/08	Modify Rated Current	GH	OPERATION	DRAW	DATE	SCALE	1:1	PART NO.
B0	2020/11/12	Add W/T WCON LOGO SPEC&P/N	XSR	x.xx ±0.40	GH	2023/12/08	UNIT	mm	3910-SXXX-062MXXWRX(W) Δ
A5	2019/12/12	Modify	XSR	x.xx ±0.25	CHECK	DATE	SIZE	A4	TITLE: Δ 1.27mm Pitch SDC CONNECTORS FEMALE "E" TYPE, H=6.2(TYPE B)
A0	2017/08/28	NEW	---	x.xxx ±0.15	---	DATE	SHEET	1/1	Customer NO.
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	Angle ± 3°	APPROVE	DATE	PROJ.		
				DIM TOL					

WCON

Http: www.wcon.com

WCON-Dongguan
 Tel: +86 769 85358920
 Fax: +86 769 85358915
 E-mail: sales@wcon.com

WCON-Kunshan
 Tel: +86 512 57468408
 Fax: +86 512 57468468
 E-mail: sales@wcon.com